

## ABSTRACT

The elucidation of how populations of interest interact in a given community and how the community responds to stress and perturbations can help inform the interplay between stress pathways and gene networks that help optimize bacterial bioremediation. A goal of VIMSS is to characterize the responses of bacterial communities at multiple levels of resolution in order to understand biochemical capacity at DOE waste sites. The current work uses a series of re-circulating wells that create a subsurface bioreactor to stimulate microbial growth for *in situ* U(VI) immobilization (Wu et al. ES&T 41:5716-5723). Bacterial community dynamics were investigated in a series of re-circulating wells that created a subsurface "bio-reduction zone" to stimulate bacterial growth with ethanol for *in situ* bioremediation of U(VI) at the Field Research Center of the U.S. Department of Energy, Oak Ridge, TN. Different experiments were conducted to alter the subsurface environment to better understand strategies that would improve the remediation process. Within this framework, the interrelationships between the biogeochemistry were studied in order to characterize the community and ecosystem ecology with respect to microbiology of an engineered system. Bacterial community composition and structure of groundwater samples were analyzed via clone libraries of partial SSU rRNA genes. UniFrac analyses showed that the bacterial community in each of the wells developed changes during the bioremediation process, and the changes could be attributed to the variations along temporal and spatial scales. Relationships between community diversity and ecosystem function were idiosyncratic, and these results suggested the population distributions depended on the particular conditions under which the local landscape was investigated. Principal component analysis showed that nitrate, uranium, sulfide, sulfate, and COD were strongly associated with particular bacterial populations. Sequences closely related to nitrate-reducing bacteria were predominant during the initial phase of the remediation process, but sequences representative of sulfate-reducers (*Desulfovibrio* and *Desulfosporosinus* spp.) and metal-reducers (*Geobacter* spp.) were detected at higher levels after uranium levels declined. Ultimately, sequences associated with sulfate-reducing populations predominated. Uranium levels declined below EPA drinking water standards, and community composition and structure were similar in both treatment wells after approximately 1.5 y despite going through different transitions. In addition, when engineering controls were compared to the community structure and composition via canonical ordinations, population distributions could be related with dissolved oxygen control and the presence of bio-stimulant. During the bio-stimulation, population distributions followed geochemical parameters, and these results indicated that bacteria exhibited distributions at the landscape scale in concordance with predictable geochemical factors. The data indicated that relationships between community structure and ecosystem function were idiosyncratic, but temporal and spatial concordance were eventually observed for the two bio-stimulated wells. The strong associations between particular environmental variables and certain population distributions will provide insights into establishing practical and successful remediation strategies in radionuclide-contaminated environments with respect to engineering controls and ecosystem function.


## Map of the Oak Ridge Field Research Center.



## View of S-3 ponds before and after capping in to a parking lot.




Map and photos courtesy of U.S. DOE Oak Ridge-ERC.



**Area view of well design at Area 3.** A series of re-circulating wells establish a subsurface bioreactor to stimulate microbial growth for *in situ* U(VI) immobilization. Well FW-104 is the injection well for the electron donor (ethanol); well FW-026 is the extraction well for the recirculation loop; well FW-101 is the center of biostimulation; and FW-024 and FW-103 are upstream and downstream wells, respectively.

## RESULTS



Uranium U(VI) concentrations in groundwater of monitoring wells over time in the bio-reduction zone. Nitrate levels were below 0.20 mM between 200 and 350 d, peaked to 1.5 mM between 350 and 500 days, and fell below 0.1 mM after day 500.

